

KRYPTON PROLINE THINNER



Solvent for Krypton single-component polyurethane moisture-cured anti-corrosion

DESCRIPTION

Krypton ProLine THINNER is a slow-evaporation solvent thinner for Krypton's moisture-cured, single-component anti-corrosive polyurethane: Recommended for thinning:

- Krypton ProLine PU ZN primer
- Krypton ProLine PU AL primer
- Krypton ProLine AC MIO
- Krypton ProLine SILVER TC

TECHNICAL DATA

PRODUCT INFORMATION BEFORE APPLICATION

Chemical identity	Mixture of organic solvents
Physical state	Liquid
Presentation	Metal container: 5/10 litres
Flash point	27°C (ASTM D 93)
Colour	Transparent
Density	0.9 g/cm ³ (20°C)
VOC (g/L and %)	819.18 g/L, 100%
Water determination, ISO 12937	< 0.04%
Storage	Store between 5-35°C, protected from sources of ignition
Expiry	12 months after the date of manufacture

AS A THINNER

Add to the paint material and stir thoroughly beforehand with a low-speed mixer in order to achieve completely homogeneous conditions.

Cleaning
It can be used as a cleaner.

ENVIRONMENTAL CONDITIONS

According to Krypton ProLine THINNER TDS.

PRODUCT STORAGE

The product must be stored in its original containers, tightly closed. Storage conditions require keeping the containers in a dry, well-ventilated place away from sources of heat or ignition.

SAFETY

Use with adequate ventilation. Do not inhale the aerosol. Avoid contact with skin. In case of contact with skin, wash immediately with detergent, soap and water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice immediately.

ENVIRONMENTAL PRECAUTIONS

Empty containers should be handled with the same precautions as if they were full. Containers should be considered hazardous waste and transferred to an authorised waste disposal company.

ADDITIONAL INFORMATION

The information contained in this TECHNICAL DATA SHEET, as well as our advice, whether written, verbal or provided through testing, is given in good faith based on our experience and the results obtained through testing carried out by independent laboratories, and does not serve as a guarantee for the user, who should take it as a guide and for information purposes only.

We recommend that you study this information in depth before using and applying any of these products, although it is particularly advisable to carry out tests on site to determine the suitability of a treatment in that location, for the purpose and under the specific conditions of each case.

Our recommendations do not exempt the applicator from the obligation to have in-depth knowledge of the correct method of application of these systems before proceeding to use them, as well as to carry out any preliminary tests that may be appropriate if there is any doubt as to their suitability for any work, installation or repair, taking into account the specific circumstances in which the product is to be used.

The application and use and processing of our products are beyond our control and are therefore the sole responsibility of the installer. Consequently, the applicator shall be solely and exclusively liable for any damage or loss resulting from total or partial failure to comply with the user and installation manual and, in general, from the inappropriate use or application of these products.

This technical data sheet supersedes all previous versions.



KRYPTON CHEMICAL SL

C/ Martí i Franquès, 12 - Pol. Ind. les Tàpies
43890 - l'Hospitalet de l'Infant - Spain
Tel: +34 977 822 245 - Fax: +34 977 823 977
www.kryptonchemical.com - rayston@kryptonchemical.com

Last revision:

11/12/2025

Page:

1/1